

2014 | KBA RAPIDA RA 106 6 L FAPC ALV3

+ USED PRINTING MACHINES Ⓞ ROK: 2014 📄 6 COLOUR + COATER



Opis drukarki

EKWIPUNEK

- CX equipment (additional equipment for cardboard until 1.2 mm)
- Qualitronic ColorControl
- Intercommunication system between infeed and delivery
- CleanTronic Synchro for parallel washing for rollers and blankets cylinders
- SIS Sensoric Infeed System
- Wall screen for visualisation of all press settings
- Ergotronic LAB (Colour measurement and control according to LAB values)
- Quali Tronic Live View
- Dust Removal in the Infeed
- EES - Emission Extraction System
- Wall screen for visualisation of all press processes
- ErgoTronic Lab - Color measurement and control acc. to Lab values
- QualiTronic Quality Pass - Creation of colour measurement reports for quality control

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

☎ +34 682 639 187

✉ info@machinex.com

 **MACHINEX**




SZCZEGÓŁY TECHNICZNE

- Sheet Counter : 175 Million
- Print output : 20,000 sh/h
- Stock Thickness :: 40g/m² - 1,2 mm
- Max. format : 740 x 1060 mm
- Min. format :: 340 x 480 mm

- camera for register setting
- Additional package "Active air-cooling for control cabinets"
- Extended delivery 3800 mm (ALV 3)
- Pallet for Nonstop, plastic material
- Blower cassette for cardboard sheet guiding
- Fully-automatic plate change FAPC, incl. one pneumatic plate bending device at the gallery
- Additional package "High efficiency antistatic equipment"
- QualiTronic LiveView - Display of a "live" image of each printed sheet
- QualiTronic Quality Pass - Creation of colour measurement reports for quality control
- 1 Coating unit (L) with chambered doctor blade system
- ErgoTronic ColorDrive - Ink density measurement along the x-axis at the ErgoTronic console
- QualiTronic ColorControl (straight printing) - Inline ink density measurement
- Additional package "High-Speed" for straight-printing presses 20.000 sh/h
- KBA VariDry IR/HotAir in delivery and extended delivery (ALV3)
- Combi-Cooling Unit with Remote Condenser and FloClear Filtration System
- Air Cabinet with water heat exchanger (for water cooling)
- Varnish supply and cleaning system for water-based varnish, with operation via control console, pump output dependent on viscosity (HARRIS & BRUNO)
- Dryer connection for final and intermediate dryers
- In-line tower coater

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com



SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com

