

2002 | MAN ROLAND R 906 6 LV HYBRID

 STAMPA OFFSET  ANNO: 2002  6 COLOR + COATER



Descrizione della stampante

ATTREZZATURE

- Chromed impression cylinders
- ROLAND DELTAMATIC dampening system
- Extended Delivery
- TECHNOTRANS
- Automatic blanket, roller and impression-cylinder washing device
- Electromechanic double-sheet control
- Controllo elettromeccanico a doppio foglio
- PPL Cambio semiautomatico delle lastre
- PECOM Press Centre
- Grapho Metronic Ink Temperature Control
- Collegamento di prestampa con JobPilot PressMonitor
- RCI Remote Ink Control with CCI
- Steel Plate in feeder and Delivery
- Infrarossi + Essiccatore ad aria calda
- Performance Package for cardboard printing



DETTAGLI TECNICI

- Contatore (Milioni) : 249 Million
- Formato massimo : 1.020 x 1.420 mm
- Stampa in uscita fogli all'ora : 13.000 s.p.h
- Formato mínimo :: 600 x 850 mm
- Formato di stampa max.: 990 x 1.400 mm
- Piastre Lunghezza x larghezza: 1.140 x 1.410 mm

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com



- Air Glide Delivery
- Suction feed board
- Atlas Copco GA 77 FF
- 6 Color + Varnish
- Roland Seccomatic
- LCS Low Coverage Stabilisation
- ProfitPlus package
- Automatic Non Stop version in the delivery
- Corrugated Cardboard Package printing on thin corrugated cardboard up to 1.2 mm (G- and F-channel)
- Hybrid equipment with 2 UV Interdeck + 3 UV Lamps in delivery + IR-Hot air dryer in delivery
- Raised (500 mm)
- Water base coating: chambered ductor system + Anilox rollers

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com



2007 | MAN ROLAND R 704 3B P LV HIPRINT

 STAMPA OFFSET  ANNO: 2007  4 COLORI + VERNIC



Descrizione della stampante

ATTREZZATURE

- Chromed impression cylinders
- Grafix Hitronic powder spray
- Quick Change coating
- ROLAND DELTAMATIC dampening system
- Preset - automatic size device
- TECHNOTRANS
- APL automated plate loading (fully automatic)
- Automatic blanket, roller and impression-cylinder washing device
- Controllo della temperatura dell'inchiostro ITC
- High Pile delivery
- Controllo elettromeccanico a doppio foglio
- LCS and Quickstart
- RCI Remote Ink Control with CCI
- HiPrint Model
- Steel Plate in feeder and Delivery



DETTAGLI TECNICI

- Formato massimo : 740 X 1040 mm
- Perfezionamento: 2 + 2 - 4 + 0
- Contatore (Milioni) : 145 Million
- Formato mínimo :: 340 x 480 mm
- Stampa in uscita fogli all'ora : 15.000 sph.

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com



- CombiStar (Technotrans Beta C 400) (with Alcosmart)
(Air-cooled)
- Select Dryer IR/TL
- CIP3 connection to console and software

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com



SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com

