

# 2013 | KBA RAPIDA RA 106 6 LTTL FAPC ALV3 (18.000 )

+ USED PRINTING MACHINES    ⌚ YEAR: 2013    📄 6 COLOR + DOUBLE COATER



## Printer description

Ideal for Industry of Food packaging

## EQUIPMENT

- All Wash Up Devices
- Double sheet control - ultrasonic
- CIP Link with online connection
- VARIDAMP alcohol dampening
- Intercommunication system between infeed and delivery
- CleanTronic Synchro for parallel washing for rollers and blankets cylinders
- Coating unit with doctor chamber blades + Anilox roller
- Ink temperature control
- ErgoTronic ICR (register control)
- Lack Unit (Harris & Bruno)
- Chromed cylinders
- Automatic feeder height adjustment
- ACS (Air-Cleaning-System)
- Ergotronic LAB (Colour measurement and control)



## TECHNICAL DETAILS

- Max. format : 740 x 1060 mm
- Min. format :: 340 x 480 mm
- Print output : 18.000 s.p.h.
- Stock Thickness :: 0,06 up to 0,8 mm

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

☎ +34 682 639 187

📧 info@machinex.com




- Qualitronic PSO match (Colour control according to the PSO)
- 2 Coating unit (L) with chambered doctor blade system
- Anilox loader – Anilox roller change for 3 anilox rollers in the coater
- Varnish supply and cleaning system for water-based varnish and UV-varnish, with operation via control console, pump output dependent on viscosity (HARRIS & BRUNO)
- Additional anilox roller (according to KBA standard)
- KBA VariDry BLUE IR/HotAir/UV in delivery and extended delivery (ALV3)
- Motorized console height adjustment with memory function
- Wall screen for visualisation of all press processes
- ErgoTronic Lab - Color measurement and control acc. to Lab values
- QualiTronic KBA Control Strip 2012
- Machine oil for drive gears
- Additional package "Active air-cooling for control cabinets"
- Drying unit (T) for straight-printing presses
- Extended delivery 3800mm (ALV 3)
- Fully-automatic plate change FAPC, incl. one pneumatic plate bending device at the gallery
- IPA reduction < 5% incl. microfilter "beta.f" (TECHNOTRANS)
- ErgoTronic ColorControl - Automatic ink density measurement along x and y axis at the ErgoTronic console
- Kba PressSupport 24 Sheetfed with internet connection for remote maintenance and software updates
- Additional package "High efficiency antistatic equipment"
- QualiTronic Quality Pass - Creation of colour measurement reports for quality control
- SIS – Sensoric Infeed System, sidelay-free lateral sheet alignment with automatic format setting via ErgoTronic console, lateral alignment occurs by means of movable infeed gripper bar
- Inking unit temperature control without ink duct roller cooling, incl. High-tech combi-cooling unit, air-cooled (TECHNOTRANS)
- Roller covering for alcohol-reduced printing
- KBA VariDry IR/HotAir in the drying unit
- QualiTronic ColorControl (straight printing) - Inline ink density measurement
- Varnish supply and cleaning system for water-based varnish, with operation via control console, pump output dependent on viscosity (HARRIS & BRUNO)

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 [info@machinex.com](mailto:info@machinex.com)

