

2008 | KBA RAPIDA RA 105 8 SW 4

+ DRUCKMASCHINEN (OFFSET) Ⓞ JAHR: 2008 📄 8 FARBEN



Druckerbeschreibung

AUSRÜSTUNG

- double sheet control - electronic
- Electromechanic double-sheet control
- Intercommunication system between infeed and delivery
- Modell P-40 (18.000 Geschwindigkeit pro Stunde)
- Baldwin blanket, roller, and impression cylinder wash-up device
- Technotrans Beta C High Tech Combi cooling device
- Kersten antistatic high performance version
- Pile entry in sheet travel direction
- ErgoTronic ACR - Automatic Camera Register, video camera for register setting
- Fully-automatic plate change FAPC, incl. one pneumatic plate bending device at the gallery
- PowderStar AP 262 Pudergerät
- SIS - Sensoric Infeed System, ziehmarkenfreie seitliche Bogenausrichtung mit automatischer Formateinstellung über ErgoTronic-Leitstand, die seitliche Ausrichtung erfolgt über eine bewegliche Einlaufgreiferleiste



TECHNISCHE DETAILS

- Laufleistung : 295 Million
- Maximale Geschwindigkeit Bg./h : 18.000 s.p.h.
- Stärke :: 60 g/m² up to 600 g/m²
- Max. Bogenformat : 740 x 1,050 mm

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

☎ +34 682 639 187

✉ info@machinex.com



SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com



SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com

