

2015 | KBA RAPIDA RA 106 6 L ALV2 SIS FAPC CX

 STAMPA OFFSET  ANNO: 2015  6 COLOR + COATER

Descrizione della stampante

LED UV AMS<>Press raise 450 mm<>Wallscreen<>Inmould Foil Package<>Hybrid equipment<>Double extended delivery ALV2<>Infeed sensors for black substrates<>Pile entry in sheet travel direction<>Drivetronic SPC<>Drivetronic Plate Ident<>Flying job change<>DriveTronic SRW (UV) Simultaneous Roller Washing<>DriveTronic SFC Simultaneous Form Change<>Cleantronic Synchro multipurpose washing system for all washers in case of using changing types of ink<>Cleantronic UV<>Harris&Bruno varnish supply and cleaning system for water based varnish and UV varnish<>Anilox loader – Automatic anilox roller change for 3 anilox rollers in the coater<>Pile exit in operating drive S1<>Dryer air exhaust<>EES Emission Extraction system<>KBA Varidry UV/ IR/ Hot air dryer in delivery and extended delivery<>3 x Exchange positions for UV interdeck in unit 1,4 and 6<>Qualitronic ColorControl<>Qualitronic Dotview<>Qualitronic Quality Pass<>Ergotronic ColorControl<>ErgoTronic ACR Automatic Camera Register<>ErgoTronic ICR Integrated Camera Register<>Preparation for sheeter<>Preparation for Vinfoil Modul<>No Compressor (house air)<>Ink temperature control water cooled<>FAPC automatic plate change<>CX package for cardboard up to 1.2mm<>Colortronic (Register, Dampening and Ink Remote System Control)<>Preset - automatic size device<>Cooking register<>Antistatic complete<>anilox coater<>Technotrans Beta refrigeration<>Non-stop feeder<>INTERCOM<>SIS register system<>Non-stop delivery



DETTAGLI TECNICI

- Contatore (Milioni) : 55 Mill
- Formato massimo : 740 x 1060 mm
- Formato mínimo :: 340 x 480 mm
- Stampa in uscita fogli all'ora : 18.000 sh/h

SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com



SPAIN | GERMANY | USA | ITALY | TURKEY | CHINA | BRAZIL | MEXICO | PERU

 +34 682 639 187

 info@machinex.com

